

Q PLUS SERIES OPTIONS, SPARES & CONSUMABLES LIST

The Q Plus Series is suitable for both sputter coating metals, carbon and metal evaporation in SEM, FE-SEM and TEM applications. You can be assured, whatever your sample - the market leading Q Plus Series has it covered.



Q150 Plus Series



Q300 Plus Series

Q150V Plus Ordering Information

- 27688** Q150V S Plus Sputter Coater optimised for high-vacuum applications. High resolution turbomolecular pumped capacitive touch-screen controlled sputter coater with status LED indicator, including 10034 quick release sputter insert and one TK8845 57mm diameter x 0.3mm chromium target. 10067 rotating specimen stage, 50mm diameter, supplied as standard.
- 27685** Q150V E Plus Carbon Evaporator optimised for high-vacuum applications. Turbomolecular pumped capacitive touch-screen controlled carbon evaporator with status LED indicator suitable for TEM and SEM applications. Fitted with a carbon rod evaporation head for 3.05mm diameter carbon rods. Supplied with carbon rods (C5422 3.05mm x 300mm) and a carbon rod shaper (manual operation). 10067 rotating specimen stage, 50mm diameter, supplied as standard.
- 27621** Q150V ES Plus Combined Sputtering and Carbon Coating System optimised for high-vacuum applications. The deposition heads can be swapped in seconds and the intelligent system logic automatically recognises which head is in place and displays the appropriate operating settings. Consists of high resolution turbomolecular pumped capacitive touch-screen controlled sputter coater and carbon evaporator with status LED indicator, including quick release sputter insert and one TK8845 57mm diameter x 0.3mm chromium target, and high vacuum carbon rod evaporation coater, including quick-release carbon rod insert for 3.05mm diameter carbon rods. Coating inserts are interchangeable. 10067 rotating specimen stage, 50mm diameter, supplied as standard.

Rotary pump requirements:

13034 5m3hr-1 2 Stage Oil Sealed Rotary Vane Pump

Dry pumping option:

11540 Diaphragm pump. Vacuubrand MD1 23 L/m

Options and accessories:

Head inserts and glow discharge

10453 Additional sputter insert for quick metal change (V E and V ES version only). NB: this is an entire sputtering assembly - individual targets can also be purchased

10455 Carbon fibre insert. Supplied with 2 m C5421 carbon fibre cord.

10456 Carbon Rod Evaporation Insert. For 6.15mm diameter carbon rods.

10457 Metal evaporation and aperture insert. Including the ability to evaporate upwards or downwards (V E and V ES version only). Supplied with a pack of 10 tungsten filaments (B5230) and a molybdenum (Mo) boat.

10262 Glow discharge insert

Specimen stages

10067 50 mm Stage

10357 Tilt Stage Assembly. 50mm diameter specimen stage with adjustable tilt up to 90 degrees.

10358 Slide Stage. For glass microscope slides (up to 2 x 75mm x 25mm slides).

10360 "Rotacota" Type Stage. Variable tilt angle, planetary stage, rotational speed 8-20 rpm.

10458 4" Wafer Stage and Gearbox Flat rotation specimen stage for 4" wafers.

10787 4" Wafer stage. A flat 4"/102 mm flat, drop-in wafer stage which accepts 2", 3" or 4" wafers

23850 Tilt Stage Assembly 4"

10788 4" Stub Holder

10808 8 Place Stub Stage for 30mm and 32mm \emptyset stubs

11856 14 Place Stub Stage for 25mm and 30mm \emptyset stubs

12043 9 Place Coverslip Stage 92 mm \emptyset stage accepts nine 20 x 20mm cover slips

12305 4 Place 25mm \emptyset Stub Stage

Consumables and spare parts

27608 Additional Standard Glass Cylinder Assembly. Includes glass chamber, implosion guard and gaskets.

13530 Standard Coating Shield Assembly

27691 Extended Glass Cylinder Assembly. 220mm high (standard chamber is 133mm high). For increased source to sample distance and coating large samples.

11880 Extended Height Coating Shield Assembly

B5230 Tungsten filament basket - pack of 10 (for use with 10457 metal evaporation insert).

B5228 Molybdenum boats - pack of 10.

10454 Film Thickness Monitor (FTM) Attachment. Including oscillator, feed-through, quartz crystals and holder.

Please note, when evaporating carbon, the FTM ideally should only be used to provide a general indication of the coating thickness. It is not recommended that the FTM is used for termination of the coating process.

C5460 Film Thickness Monitor (FTM) Crystal (spare)

11540 Diaphragm Pump MD1 23 L/M

07803 Basic Oil Mist Filter (spare)

13233 1L Rotary Pump Oil (spare)

13235 5L Rotary Pump Oil (spare)

27508 O-ring (each) 2 required per coater

27607 Non-seal L Gasket

27728 Q150V ES Two Year Spares Kit.

27729 Q150V E Two Year Spares Kit.

27730 Q150V S Two Year Spares Kit

Q150T Plus Series Ordering Information

- 27648** Q150T S Sputter Coater. High resolution turbomolecular pumped capacitive touch-screen controlled sputter coater with status LED indicator, including 10034 quick release sputter insert and one TK8845 57mm diameter x 0.3mm chromium target. 10067 rotating specimen stage, 50mm diameter, supplied as standard.
- 27650** Q150T E Plus Carbon Evaporator. Turbomolecular pumped capacitive touch-screen controlled carbon evaporator with status LED indicator suitable for TEM and SEM applications. Fitted with a carbon rod evaporation head for 3.05mm diameter carbon rods. Supplied with carbon rods (C5422 3.05mm x 300mm) and a carbon rod shaper (manual operation). 10067 rotating specimen stage, 50mm diameter, supplied as standard.
- 27645** Q150T ES Plus Combined Sputtering and Carbon Coating System. The deposition heads can be swapped in seconds and the intelligent system logic automatically recognises which head is in place and displays the appropriate operating settings. Consists of high resolution turbomolecular pumped capacitive touch-screen controlled sputter coater and carbon evaporator with status LED indicator, including 10034 quick release sputter insert and one TK8845 57mm diameter x 0.3mm chromium target, and high vacuum carbon rod evaporation coater, including 10033 quick-release carbon rod insert for 3.05mm diameter carbon rods. Coating inserts are interchangeable. 10067 rotating specimen stage, 50mm diameter, supplied as standard.

Rotary pump requirements:

13034 5m3hr-1 2 Stage Oil Sealed Rotary Vane Pump

Dry pumping option:

11540 Diaphragm pump. Vacuubrand MD1 23 L/m

Options and accessories:

Head inserts and glow discharge

10453 Additional sputter insert for quick metal change (T E and T ES version only). NB: this is an entire sputtering assembly - individual targets can also be purchased

10455 Carbon fibre insert. Supplied with 2 m C5421 carbon fibre cord.

10456 Carbon Rod Evaporation Insert. For 6.15mm diameter carbon rods.

10457 Metal evaporation and aperture insert. Including the ability to evaporate upwards or downwards (T E and T ES version only). Supplied with a pack of 10 tungsten filaments (B5230) and a molybdenum (Mo) boat.

10262 Glow discharge insert

Specimen stages

10067 50 mm Stage

10357 Tilt Stage Assembly. 50mm diameter specimen stage with adjustable tilt up to 90 degrees.

10358 Slide Stage. For glass microscope slides (up to 2 x 75mm x 25mm slides).

10360 "Rotacota" Type Stage. Variable tilt angle, planetary stage, rotational speed 8-20 rpm.

10458 4" Wafer Stage and Gearbox Flat rotation specimen stage for 4" wafers.

10787 4" Wafer stage. A flat 4"/102 mm flat, drop-in wafer stage which accepts 2", 3" or 4" wafers

10788 4" Stub Holder

10808 8 Place Stub Stage for 30mm and 32mm \varnothing stubs

11856 14 Place Stub Stage for 25mm and 30mm \varnothing stubs

12043 9 Place Coverslip Stage 92 mm \varnothing stage accepts nine 20 x 20mm cover slips

12305 4 Place 25mm \varnothing Stub Stage

23850 Tilt Stage Assembly 4"

Consumables and spare parts

10454 Film Thickness Monitor (FTM) Attachment. Including oscillator, feed-through, quartz crystals and holder.
Please note, when evaporating carbon, the FTM ideally should only be used to provide a general indication of the coating thickness. It is not recommended that the FTM is used for termination of the coating process.

C5460 Film Thickness Monitor (FTM) Crystal (spare)

10422 Rotating vacuum spigot. Allows a more convenient connection of the vacuum hose to the rear of the Q150T Plus - useful for when bench depth is limited.

10429 Extended height vacuum chamber. (214 mm high - the standard chamber is 127 mm high). For increased source-to- specimen distance and for coating large specimens.

13530 Standard Coating Shield Assembly

11880 Extended Height Coating Shield Assembly

B5228 Molybdenum boats - pack of 10

B5230 Tungsten filament basket - pack of 10 (for use with 10457 metal evaporation insert)

G6260 Glass cylinder 6" diameter

10068 Additional glass cylinder assembly

O7803 Basic Oil Mist Filter (spare)

13233 1L Rotary Pump Oil (spare)

13235 5L Rotary Pump Oil (spare)

23606 Non-seal L Gasket

10447 Two-year spares kit for Q150T S Plus

10448 Two-year spares kit for Q150T E Plus

10449 Two-year spares kit for Q150T ES Plus

Q150R Plus Series Ordering Information

- 27659** Q150R S Plus Sputter Coater. Fully automatic, capacitive touch-screen controlled rotary pumped sputter coater with status LED indicator. Including 10587 quick release sputter insert and one SC502-314A 57mm diameter x 0.1mm gold target. 10067 rotating specimen stage, 50mm diameter, supplied as standard.
- 27660** Q150R E Plus Carbon Evaporator. Fully automatic, capacitive touch-screen controlled rotary pumped carbon fibre evaporation coater with status LED indicator. Including 10355 quick-release carbon fibre insert for evaporation of carbon cord. Supplied with C5421 carbon fibre cord, 10067 rotating specimen stage, 50mm diameter, supplied as standard.
- 27652** Q150R ES Combined Sputtering and Carbon Coating System. Consists of fully automatic, capacitive touch-screen controlled rotary pumped sputter coater and carbon evaporator with status LED indicator. Including 10587 quick release sputter insert and one SC502-314A 57mm diameter x 0.1mm gold target, and carbon fibre evaporation coater, including 10355 quick-release carbon fibre insert for evaporation of carbon cord. Coating inserts are interchangeable and can be swapped in seconds. The intelligent system logic automatically recognises which insert is in place and displays the appropriate operating settings. 10067 rotating specimen stage, 50mm diameter, supplied as standard.

Rotary pump requirements:

13034 5m3hr-1 2 Stage Oil Sealed Rotary Vane Pump

Options and accessories:

Head inserts and glow discharge

- 10879** Carbon rod evaporation insert for 3.05 mm Ø rods (R E and R ES only). Includes carbon rod shaper 13232 and wedge tool 2097. C5422 (3.05 mm Ø x 300 mm packet of ten) carbon rods.
- 10726** Additional sputter insert for quick metal change (RE and R ES version only). NB: this is an entire sputtering assembly - individual targets can also be purchased
- 10262** Glow discharge insert. Used to modify surface properties (e.g. hydrophobic to hydrophilic conversion) (R S and R ES versions only). Can be retrofitted.

Specimen stages

- 10067** 50 mm Stage
- 10357** Tilt Stage Assembly. 50mm diameter specimen stage with adjustable tilt up to 90 degrees.
- 10358** Slide Stage. For glass microscope slides (up to 2 x 75mm x 25mm slides).
- 10360** "Rotacota" Type Stage. Variable tilt angle, planetary stage, rotational speed 8-20 rpm.
- 10458** 4" Wafer Stage and Gearbox Flat rotation specimen stage for 4" wafers.
- 10787** 4" Wafer stage. A flat 4"/102 mm flat, drop-in wafer stage which accepts 2", 3" or 4" wafers
- 23850** Tilt Stage Assembly 4"
- 10788** 4" Stub Holder
- 10808** 8 Place Stub Stage for 30mm and 32mm Ø stubs
- 11856** 14 Place Stub Stage for 25mm and 30mm Ø stubs
- 12043** 9 Place Coverslip Stage 92 mm Ø stage accepts nine 20 x 20mm cover slips
- 12305** 4 Place 25mm Ø Stub Stage

Consumables and spare parts

- 10454** Film thickness monitor (FTM) attachment. Including oscillator, feed-through, quartz crystal holder and quartz crystals.
- C5460** Spare quartz crystal
- 10429** Extended height vacuum chamber. (214 mm high - the standard chamber is 127 mm high). For increased source-to-specimen distance and for coating large specimens.
- 10731** Rotating vacuum spigot. Allows a more convenient connection of the vacuum hose to the rear of the Q150R Plus - useful for when bench depth is limited.
- 13530** Standard coating shield assembly
- 11880** Extend height coating shield assembly
- 10068** Additional standard glass cylinder assembly. Includes standard glass chamber, implosion guard and gaskets.
- 13711** Platinum coating vacuum hose assembly. Recommended for if platinum (Pt) is to be sputtered (R S and R ES versions only)
- 10730** Two-year spares kit for Q150R Plus S.
- 10729** Two-year spares kit for Q150R Plus E.
- 10728** Two-year spares kit for Q150R Plus ES.
- 07803** Basic oil mist filter (spare)
- 13233** Pump oil 1 litre
- 13235** Pump oil 5 litre
- 23606** L Gasket (each)

Q300T D Plus Ordering Information

- 10360** Q300T D Plus Dual Target Sequential Sputtering System
Includes a 57 mm Ø x 0.3 mm chromium (Cr) target (TK8845) and a 57 mm Ø x 0.1 mm thick gold (Au) target (SC502-314A).
A flat rotation stage for 4"/100 mm wafers is included.

Rotary pump requirements:

- 13034** 5 m³/hr Pfeiffer DUO 6 two-stage rotary vacuum pump. Includes vacuum hose, coupling kit and oil mist filter.

Dry pumping options:

- 11540** Diaphragm pump. A 'dry' alternative to the standard 13034 oil-based rotary pump, complete with vacuum hose, coupling kit and oil mist filter.

- 26907** Edwards dry scroll pump nXDS10i. Pumping speed: 11.4 m³/hr.

Options and accessories:

Stage options:

- 10357** Rotating 50 mm Ø specimen stage with adjustable tilt. The platform has six specimen stub positions for 15 mm, 10 mm, 6.5 mm or 1/8" pin stubs. Stage rotation speed is variable between preset limits.

NB: Target to stage height is variable between 0-42 mm for the standard stage. When used with the extended height cylinder (optional accessory 10596) the target to stage height is an additional 87 mm.

- 10067** 50 mm Ø variable height specimen stage. Has six stub positions for 15 mm, 10 mm, 6.5 mm disc stubs.

- 10360** 50 mm Ø "Rotacota" stage. A rotary planetary-style stage with variable tilt angle from horizontal to 30°. The platform has six positions for either 15 mm, 10 mm, 6.5 mm disc stubs or 1/8" pin stubs. Rotation speed is variable between preset limits.

Note: Depending on specimen height, this stage may require the optional extended height cylinder.

- 10358** 90 mm Ø specimen stage for glass microscope slides. For up to two 75 mm x 25 mm slides or a single 75 mm x 50 mm slide). The stage can alternatively accommodate up to six 1/8" SEM pin stubs. The stage rotation speed is variable between preset limits and includes a gear box to allow the optional FTM to be used.

Consumables and spare parts

- 10779** Dual channel film thickness monitor (FTM). A fully integrated system using the Q300T D touch screen display for the control and display of all FTM functions. Allows automatic termination of the sputtering process at pre-selected thickness values. Displays rate for sputtering processes in nm/m, with a resolution of 0.1 nm. Two FTM crystal holders are fixed in the chamber to give optimal position for both targets and to coat one material per crystal. Includes two spare C5460 quartz crystals

- C5460** Spare quartz crystal.

- 10596** Extended height vacuum chamber. (214 mm H - the standard chamber is 127mm H). Recommended for increased source-to-specimen distance and for coating large specimens.

- 10422** Rotating vacuum spigot. Allows a more convenient connection of the vacuum pump hose to the rear of the coater for when bench depth is limited.

- 11223** Lockable emergency stop (e-stop) switch. This can be mounted on top of the system in a position easily accessible for the operator. It is provided with a key to release the knob after activation. NB: The addition of the e-stop does not inhibit or replace the normal on/off switch function.

- 11576** Coating shields. Can be fitted to protect large surfaces from coating deposition - easily removable for ease of cleaning.

- 10428** Full range, active vacuum gauge. Capable of measurement over the range of 1,000 mbar to 5 x 10⁻⁹ mbar. Typical ultimate vacuum of system is 5 x 10⁻⁵ mbar. Must be factory fitted.

- 11288** Spares Kit for Q300T D Plus

Q300T T Plus Series Ordering Information

10824 Q300T T Plus Triple Target, Large Chamber, Turbo-Pumped Sputter Coater
Fitted with three sputtering heads to ensure even metal deposition. Includes three 57 mm Ø x 0.3 mm chromium (Cr) sputter targets (TK8845). A 10826 flat rotation stage for 200 mm/8" and 150 mm/6" wafers is fitted as standard.

Rotary pump requirements:

13034 5 m³/hr Pfeiffer DUO 6 two-stage rotary vacuum pump. Includes vacuum hose, coupling kit and oil mist filter.

Dry pumping options:

11540 Diaphragm pump. A 'dry' alternative to the standard 13034 oil-based rotary pump, complete with vacuum hose, coupling kit and oil mist filter.

26907 Edwards dry scroll pump nXDS10i. Pumping speed: 11.4 m³/hr.

Options and accessories:

Stage options:

10357 Rotating 50 mm Ø specimen stage with adjustable tilt. The platform has six specimen stub positions for 15 mm, 10 mm, 6.5 mm or 1/8" pin stubs. Stage rotation speed is variable between preset limits.

NB: Target to stage height is variable between 0-42 mm for the standard stage. When used with the extended height cylinder (optional accessory 10596) the target to stage height is an additional 87 mm.

10067 50 mm Ø variable height specimen stage. Has six stub positions for 15 mm, 10 mm, 6.5 mm disc stubs.

10360 50 mm Ø "Rotacota" stage. A rotary planetary-style stage with variable tilt angle from horizontal to 30°. The platform has six positions for either 15 mm, 10 mm, 6.5 mm disc stubs or 1/8" pin stubs. Rotation speed is variable between preset limits.

Note: Depending on specimen height, this stage may require the optional extended height cylinder.

10358 90 mm Ø specimen stage for glass microscope slides. For up to two 75 mm x 25 mm slides or a single 75 mm x 50 mm slide). The stage can alternatively accommodate up to six 1/8" SEM pin stubs. The stage rotation speed is variable between preset limits and includes a gear box to allow the optional FTM to be used.

Consumables and spare parts

10779 Dual channel film thickness monitor (FTM). A fully integrated system using the Q300T D touch screen display for the control and display of all FTM functions. Allows automatic termination of the sputtering process at pre-selected thickness values. Displays rate for sputtering processes in nm/m, with a resolution of 0.1 nm. Two FTM crystal holders are fixed in the chamber to give optimal position for both targets and to coat one material per crystal. Includes two spare C5460 quartz crystals

C5460 Spare quartz crystal.

10596 Extended height vacuum chamber. (214 mm H - the standard chamber is 127mm H). Recommended for increased source-to-specimen distance and for coating large specimens.

10422 Rotating vacuum spigot. Allows a more convenient connection of the vacuum pump hose to the rear of the coater for when bench depth is limited.

11223 Lockable emergency stop (e-stop) switch. This can be mounted on top of the system in a position easily accessible for the operator. It is provided with a key to release the knob after activation. NB: The addition of the e-stop does not inhibit or replace the normal on/off switch function.

11576 Coating shields. Can be fitted to protect large surfaces from coating deposition - easily removable for ease of cleaning.

10428 Full range, active vacuum gauge. Capable of measurement over the range of 1,000 mbar to 5 x 10⁻⁹ mbar. Typical ultimate vacuum of system is 5 x 10⁻⁵ mbar. Must be factory fitted.

11288 Spares Kit for Q300T T Plus

Sputter Targets		Q150R PLUS	Q150T PLUS	Q150V PLUS	Q300T T PLUS	Q300T D PLUS
SC502-314A	Gold (Au)	✓	✓	✓	✓	
SC502-314A/ 0.2mm	Gold (Au) 0.2 mm	✓	✓	✓	✓	
TK8889	Gold (Au) 0.3 mm	✓	✓	✓	✓	✓
SC502-314B	Gold/palladium (Au/Pd - 80:20)	✓	✓	✓	✓	
SC502-314B/0.2mm	Gold/palladium (Au/Pd - 80:20%) 0.2 mm	✓	✓	✓	✓	
TK8891	Gold/palladium (Au/Pd - 80:20) 2 mm	✓	✓	✓	✓	✓
SC502-314C	Platinum (Pt).	✓	✓	✓	✓	
SC502-314C/0.2mm	Platinum (Pt) 0.2 mm	✓	✓	✓	✓	
TK8893	Platinum (Pt) 0.3 mm	✓	✓	✓	✓	
SC502-314D	Nickel (Ni)		✓	✓	✓	
SC502-314E	Silver (Ag)	✓	✓	✓	✓	
SC502-314G	Palladium (Pd)	✓	✓	✓	✓	
SC502-314H	Copper (Cu)	✓	✓	✓	✓	
TK8878	Platinum/Palladium (Pt/Pd - 80:20)		✓	✓		✓
TK8887	Platinum/Palladium(Pt/Pd -80:20) 0.3mm		✓	✓	✓	✓
TK8845	Chromium (Cr) 0.3 mm		✓	✓	✓	✓
TK8862	Chromium (Cr)1.5 mm		✓	✓	✓	✓
TK8867	Tungsten (W) 0.2 mm		✓	✓	✓	✓
TK8846	Tungsten (W) 0.5 mm		✓	✓	✓	✓
TK8869	Carbon (C) 1.5 mm		✓	✓	✓	✓
TK8875	Aluminium (Al) 1 mm		✓	✓	✓	✓
TK8895	Titanium (Ti) 0.5 mm		✓	✓	✓	✓
TK8879	Titanium (Ti) 1.5 mm		✓	✓	✓	✓
TK8897	Iron (Fe)		✓	✓	✓	✓
TK8899	Iridium (Ir) 0.3 mm		✓	✓	✓	✓
TK8900	Cobolt (Co) 0.3 mm		✓	✓	✓	✓
TK8902	Tin (Si)		✓	✓	✓	✓
TK8903	Molybdenum		✓	✓	✓	✓
TK8905	Magnesium (Mg) 0.3 mm thick		✓	✓	✓	✓
TK8906	Tantalum (Ta)		✓	✓	✓	✓
TK8907	Indium tin oxide (ITO)		✓	✓	✓	✓
TK9000	Alluminium (Al) 0.76mm					✓
TK8870	Copper (Cu) 1.5 mm					✓
TK8859	Gold (Au) 0.1 mm					✓
TK8860	Gold/palladium (Au/Pd) 0.1 mm					✓
TK8872	Nickel (Ni) 0.1 mm					✓
TK8877	Palladium (Pd) 0.1 mm					✓
TK8861	Platinum (Pt) 0.1 mm					✓
TK8871	Silver (Ag) 0.1 mm					✓
Carbon Supplies		Q150R PLUS	Q150T PLUS	Q150V PLUS	Q300T T PLUS	Q300T D PLUS
A0830A	Carbon rods 6.15 mm Ø x 100 mm length (unshaped) - pack of 10	NA	✓	✓	NA	NA
C5422	Carbon rods 3.05 Ø x 100 mm, (unshaped) - pack of 10	✓	✓	✓	NA	NA
C5421	Carbon fibre cord - 1 m	✓	✓	✓	NA	NA
C5421-10	Carbon fibre cord - 10 m	✓	✓	✓	NA	NA
C5421-100	Carbon fibre cord - 100 m	✓	✓	✓	NA	NA
C5461	Carbon fibre - fine strands (1m)	✓	✓	✓	NA	NA
C5461-10	Carbon fibre - fine strands (10m)	✓	✓	✓	NA	NA
C5461-100	Carbon fibre - fine strands (100m)	✓	✓	✓	NA	NA
13232	Manual carbon rod shaper for 3.05 mm Ø carbon rods	✓	✓	✓	NA	NA
10879	Carbon gun insert 3.05 mm	✓	✓	✓	NA	NA
12097	Wedge tool	✓	✓	✓	NA	NA

The Q Plus Series has it covered: quorumtech.com

The Q Plus Series

Features	Q150R PLUS	Q150T PLUS	Q150V PLUS	Q300T T PLUS	Q300T D PLUS
New touch and swipe capacitive screen	✓	✓	✓	✓	✓
USB port for upgrades and download of log files	✓	✓	✓	✓	✓
Multiple-user profiles can be set up on one machine	✓	✓	✓	✓	✓
New software sorts recipes per user according to recent use	✓	✓	✓	✓	✓
16GB of flash memory can store more than 1000 recipes	✓	✓	✓	✓	✓
Status indication through visual multi-colour LED	✓	✓	✓	✓	✓
Audio notification when process completed	✓	✓	✓	✓	✓
Create recipe sequences with simple copy, drag and drop operation	✓	✓	✓	✓	✓
Interchangeable stage options	✓	✓	✓	✓	
Interchangeable plug-in heads	✓	✓	✓		
Capable of achieving vacuum 2×10^{-3} mbar	✓	✓	✓	✓	✓
Capable of achieving vacuum 5×10^{-5} mbar		✓	✓	✓	✓
Capable of achieving vacuum 1×10^{-6} mbar			✓		
FTM control on carbon deposition as an option		✓	✓		
Three sputter heads for large area deposition of different materials				✓	
Single head selection for small samples				✓	✓
Multi-layer deposition of two materials					✓

Benefits	Q150R PLUS	Q150T PLUS	Q150V PLUS	Q300T T PLUS	Q300T D PLUS
Single system for sputter and carbon coating	✓	✓	✓		
Easy selection for frequently used recipes	✓	✓	✓	✓	✓
Easy configuration of head and stage options for different samples	✓	✓	✓		
Easy to see multi-colour status indicator light from a distance	✓	✓	✓	✓	✓
Ultra-fine grain size coating capability		✓	✓	✓	✓
Ultra-fine carbon coating for high-resolution applications using carbon rods			✓		
High purity depositions			✓		
Large area of depositions - up to 200mm diameter				✓	

Recommended Applications	Q150R PLUS	Q150T PLUS	Q150V PLUS	Q300T T PLUS	Q300T D PLUS
Low and medium magnifications	✓				
SE Signal boost (1nm or less)	✓				
Table-top SEM coating	✓				
Elemental analysis	✓				
Copper metallisation of layers	✓				
High-resolution magnification SEM		✓			
Protective platinum layers for FIB		✓			
R&D of corrosion-, friction-, and wear- protective layers		✓	✓		
Protective layers on medical devices		✓	✓		
Carbon coating of replicas		✓	✓		
BSE imaging		✓	✓		
EDX, WDS, EBSD analysis		✓	✓		
Carbon coating of TEM grids			✓		
Ultra-high resolution magnification SEM			✓		
Nano-technology e.g. Zeolites, polymer nanobrushes			✓		
Wafer inspection				✓	
Multiple sample prep for SEM				✓	
Materials applications - ideal for multi-layer coatings					✓

QSeries Rev 0 - 17.10.18



+44 (0)1323 810981

sales@quorumtech.com

quorumtech.com

Products are for Research Use Only. While every effort has been made to ensure accuracy, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation and you are strongly advised to obtain copies of the most recently issued regulations, standards and guidelines. This document does not form the basis of a contract. Quorum has a policy of ongoing product improvement and reserves the right to change specifications without notice. © 2018 Quorum Technologies Limited. All rights reserved.